



Application Instruction:

1. Al Ahli joint compound can be applied for drywall gaps, joints, and screw spots. The consumption for finishing is about 4 square meter (m²) per container. The consumption for filling the joint is about 20 linear meters per container.
2. Do not mix Al Ahli joint compound with other materials.
3. The surface should be stable and dry.
4. Remove any dust with the brush to clean the surface.
5. Fix drywall joint tape and fold it to fit at a correct angle for the corners.
6. If the Al Ahli joint compound has hardened, add clean water and remix before use.
7. Once the liquid and compound have separated, mix again with a mixer.
8. Apply by hand with a drywall spatula or trowel.
9. Use several coats of joint compound to make the surface perfectly smooth and even.
10. Let each coat dry completely before applying the next coat and before final sanding.

Storing condition:

Protect against direct sunlight and extreme cold. The containers should be kept above 5°C and below 35°C. Unopened containers can be stored in standard condition for 12 months.

Health and safety:

Ensure proper ventilation during application and drying. Wear eye protection, face masks, and gloves to avoid breathing problems and skin irritation. Store out of reach of children.

Application

- Ready to use for interior filler and skim coat.
- Easy to apply / Smooth Finish / made in iran.

Al Ahli Trading Contact
Tel: + 971-42 52 3230
Mobile: + 971-55 120 9995
Address: 207 Kasco Tower, Damascus
Street Al Qusais Industrial Area 3,
Dubai, UAE
Email: sales@alahitrading.com
www.alahitrading.com

■ 28 KG ■ 25 KG