



AL Ahli Multi-Use Joint Compound - TDS

AL Ahli Multi-Use Joint Compound is an air-drying, compound suitable for all three coat applications or as a finishing coat for all plasterboard joints, angles and fastener heads. Complies with ASTM C475.

PRODUCT FEATURES

- Premium grade, all purpose or finishing compound.
- Used for all three coats or as a skimming coat.
- Excellent workability, easy application by hand or with mechanical tools.
- Minimal mixing & cleaning of tools.
- Can be sanded by hand or with mechanical sanding tools.
- Excellent surface for painting.

PRODUCT INFORMATION

Color	White
Working Time	Drying Type: Minimum 24 hours drying time or longer in adverse climatic conditions
Packaging	28kg
VOC content	<50g/L
Tapping & Filling Coverage	50m ²

APPLICATION

- Surfaces must be clean and free from dust.
- AL Ahli Multi-Use Joint Compound may be diluted to a workable viscosity by adding water followed by mechanical mixing if desired. • Can be applied by hand or mechanical tools.
- When using AL Ahli Multi-Use Joint Compound for all three coats, the first coat must be used to bed a high-quality paper tape.
- AL Ahli Multi-Use Joint Compound must be allowed to dry thoroughly (up to 24 hours depending on temperature & humidity) before re-coating or sanding.
- Only apply over setting type compounds that have been allowed to dry thoroughly.
- Sand with care using 180 or 220 grit paper.
- Thoroughly clean all tools and equipment after use.

